


DOUBLE HINGED, HO70D A60 FIRE RATED DOOR

H070D



RAPP BOMEK H070Ddoors are designed and manufactured to meet the requirement in SOLAS 74 and IMO FTP code.

According to NORSOK C-002, M2, H1 and H2. Door type code:

Certification: Class societies type approved

Fire rating: Non-Rated, AO and A60

RBFDH070D Part no:

Door leaf: The door leaf is constructed of an outer shell of 3 mm thick steel plate

on both sides of an insulating core. The door leaf is internally stiffened

using angle profile.

The total leaf thickness is 106 mm.

Reinforcement plates for Hinges and Door closer are provided to the

door leaf plates.

Door frame: The door frame is made of 4 mm steel plate, Z-shaped according to

the drawing.

The door leaf and frame are made of either mild steel or stainless Material:

Mild Steel finished with NORSOK M501 painting system.

Stainless Steel brushed finished.

Hinges: The hinges are special designed and are made of stainless steel

AISI 316L.

The hinges are welded to the frame and bolted to the door leaf.

Each door leaf has 4 hinges with grease nipple.

Handle: The Handle is of type Rapp Bomek HD-handle stainless steel quality

AISI 316L.

Latch: Active doorleaf: The Latch is of type Rapp Bomek 4 points and are made of

stainless steel AISI 316L, externally fitted to the door leaf with a protection

Passive door leaf is supplied with stainless steel stretching latch

(espagnolette). A central handle operate mortise bolts at top and bottom of

the door leaf.

Door closer: The door closer is of heavy duty type DORMA TS 83 / EN7, adjustable,

Active doorleaf only.

Gasket: The fire gasket between door leaf and frame is made of silica fibre.

Installation: Bolted installation. The door frame is pre-drilled for bolted installation.

Installation bolts M12x35 with nut, washer and 3x30mm gasket.

Sound rating: Rw 43dB.

CO=1200x2100, estimated to 400kg Weight:

Marking of To comply with NORSOK C-002, edition 4, chapter 7.10 and 7.16 and DNV's product:


requirements for marking of products, the door leaf is provided with a

tag/door sign to fulfill these requirements.

Hardware and accessories adapted to the door type, on request.



DOUBLE HINGED, H070D A60 FIRE RATED DOOR



Abbreviations: COW - Clear Opening Width

COWA - Clear Opening Width Active door leaf COWP - Clear Opening Width Pasive door leaf

COH - Clear Opening Height SOW - Structural Opening Width SOH - Structural Opening Height